Wireless N PTZ Internet Camera

TV-IP651W (v1.0R)

The Wireless N PTZ Internet Camera, model TV-IP651W, provides security over a large area. Pan the camera side-to-side a remarkable 340 degrees and tilt up-and-down 115 degrees from any Internet connection.

Wireless n technology provides unsurpassed wireless coverage and improved streaming video quality. Add this camera to your wireless network at the touch of a button with Wi-Fi Protected Setup (WPS).

Record 640 x 480 pixel (VGA) video at up to 20 frames per second (fps). Manage up to 32 TRENDnet cameras with the included complimentary camera management software. Advanced features include adjustable motion detection recording areas, email alerts, scheduled recording sessions, pan / tilt Auto-Patrol, date-and-time overlays, one-way audio, an adjustable lens, and four times digital zoom. A wall / ceiling mounting kit is included and the camera's off white housing blends into most environments.

PRODUCT OVERVIEW

- Pan 340° side-to-side and tilt 115° up-and-down
- High speed wireless n connection
- Program motion detection recording, recording schedules, email alerts and more with complimentary software
- 1-way audio

FEATURES

- Wi-Fi compliant with IEEE 802.11n standard
- Backwards compatible with IEEE 802.11g and IEEE 802.11b devices
- One touch WPS connection button
- 1 x 10/100Mbps Auto-MDIX RJ-45 port (for optional wired installation)
- Power and activity LED indicators (can be disabled)
- 1-way audio
- 4x digital zoom
- Pan left or right 170° for a total of 340°
- Tilt the camera up 90° and down 25° for a total of 115°
- Dynamic DNS support
- Supports up to 640 x 480 pixel resolution at up to 20 frames per second
- Image controls: Brightness, contrast, saturation, flip image vertically, mirror image horizontally
- Define a recording schedule or motion detection recording
- Create motion detection fields of any shape over the viewing area
- Supports TCP/IP networking, Email, HTTP, and other Internet protocols
- System controls:
  - Define up to 64 user login accounts
  - Set the date and time or synchronize with an NTP server
- Supports wireless encryption up to WPA2-PSK
- Quick Universal Plug and Play (UPnP) installation
- Complimentary SecurView™ Pro software: manage up to 32 cameras *
- SecurView™ Pro software compatible with Windows operating systems
- Mounting base and mounting hardware included
- 3-year limited warranty

*Monitoring multiple cameras may require a high performance CPU

SECURVIEW PRO CAMERA SOFTWARE FEATURES

- Manage up to 32 cameras
- Compatible with Windows and Microsoft Server 2008
- Multiple language support
- Camera Viewing
    - Preset viewing modes
    - Program custom viewing modes
    - Full screen view
    - Drag and drop live feeds to a new location
    - Program camera cycle viewing sequence
    - Motion detection brings video forward
    - Side, top, and bottom tool bars can be hidden
    - Web based access from smart phones and tablets
- Recording options
    - Program weekly recording schedules
    - Motion detection recording
        - Define motion detection areas of any shape
        - Define motion detection sensitivity
    - Event trigger recording
    - Date and time overlay
    - Mask overlay to conceal sensitive areas
    - Save a single video stream to multiple locations simultaneously
    - Define recording quotas by recording time or space allocation
    - Disk clean feature condenses and optimizes old files
    - Real time recording stats to help manage files
- Search and Playback
    - Navigation timeline provides a quick visual reference to the recorded content
    - Search continuous recordings by motion
    - Search recordings by motion within a defined field (a portion of the viewing area)
    - Time laps playback search
- Map cameras on an image such as a floor plan
- Map cameras on Google Maps™

Wireless N PTZ Internet Camera

TV-IP651W (v1.0R)

SPECIFICATIONS

CAMERA	

General	• Sensor: 1/5" CMOS Sensor
	• Board Lens
	• Focal Length: 4mm
	• F/No: 1.5
	• Minimum illumination: 1 lux
	• Focus Depth: 20 cm ~ infinity
	• View:
	  • Horizontal: 38.0 degrees
	  • Vertical: 28.7 degrees
	  • Diagonal: 46.5 degrees
	• Digital Zoom: 4x

Audio	• Built-in omni-directional microphone • Sensitivity: -38dB +/- 3dB (5 meters max.) • Frequency: 10~20000Hz • S/N: >60dB • Format: PCM
Pan & Tilt	• Pan: -170° ~ +170° • Tilt: up 90°and down 25° • Auto-Patrol preset positions: 24
HARDWARE	
Network	• IEEE 802.3u 10/100Mbps Auto-MDIX Fast Ethernet
LED	• Power, Link/Act
WPS Button	• Push to enable WPS
Reset Button	• Reset to factory default
Privacy Button	• Privacy mode on / off
Power Consumption	• Max 6.12 Watts
Power	• Input: 100~240V, 50/60Hz, 0.5A • Output: 12V, 1.25A external power adapter
Dimension	• 113 x 113 x 130 mm (4.5 x 4.5 x 5.1 in.)
Weight	• 503 g (1.1 lbs.)
Temperature	• Operating: 0°C ~ 40°C (32°F ~ 104°F) • Storage: -25°C ~ 70°C (-13°F ~ 158°F)
Humidity	• Max. 90% (non-condensing)
Certifications	• CE, FCC
REQUIREMENT	
Management Interface	• Internet Explorer 7.0 or higher • Firefox 3.5 or above • Safari 4.0 or above
To Run software	• Windows 7 (32/64-bit), Vista (32/64-bit), XP (32/64-bit) • Windows Server 2003, 2008
SecurView Pro Software	• Channel: supports up to 32 cameras • Record / Playback / Motion Detection/Audio
Network Protocols	• IPv4, ARP, TCP, UDP, ICMP • DHCP Client, NTP Client, DNS Client, DDNS Client, SMTP Client, FTP Client • HTTP • PPPoE • UPnP

Wireless N PTZ Internet Camera

TV-IP651W (v1.0R)

SPECIFICATIONS

WIRELESS	
Standard	• IEEE 802.11b, IEEE 802.11g, and IEEE 802.11n
Frequency	• 2.4 ~ 2.497 GHz ISM band
Antenna	• 1 x detachable 2dBi dipole antennas (Reverse-SMA connector)
Date Rate	• 802.11b: up to 11Mbps • 802.11g: up to 54Mbps • 802.11n: up to 150Mbps
Security	• 64/128-bit WEP, WPA / WPA2-PSK
Output Power	• 802.11b: 18dBm (typical) • 802.11g: 15dBm (typical) • 802.11n: 15dBm (typical)
Receiving Sensitivity	• 802.11b: -85dBm at 11Mbps • 802.11g: -76dBm at 54Mbps • 802.11n: -65dBm at 150Mbps
Channels	• 1~11 (FCC), 1~13(ETSI)
MANAGEMENT	
Accounts	• Up to 64 user accounts
Remote Login	• Remote management supported
Backup / Restore	• Save / retrieve configuration files
SETTINGS	
Image	• Brightness, contrast, saturation, flip, mirror (horizontal / vertical)

Video Setting	• Encoding: MJPEG
	  • Resolution: 640 x 480 (20 fps), 320 x 240 (30 fps), 160 x 120
	  • Max frame rate: VGA @ 20fps, QVGA @ 30fps, QQVGA @ 30fps
	  • JPEG quality: Very Low, Low, Medium, High, Very High

Recording	• Event based (motion detection) and scheduled
Snapshot	• Trigger event: motion detection • Action: send alert email and / or upload to FTP • Real time snapshot
Port Settings	• HTTP port: 80 (default)
Time	• Synchronize with NTP server or set time / date manually

Wireless N PTZ Internet Camera

TV-IP651W (v1.0R)

NETWORKING SOLUTIONS

PACKAGE CONTENTS

- TV-IP651W
- CD-ROM (Utility & User's Guide)
- Multi-Language Quick Installation Guide
- Network cable (1.5 m / 5 ft.)
- Power adapter (12V DC, 1.25A)
- Camera mounting kit

RELATED PRODUCTS

TV-IP651WI	Wireless N Day / Night PTZ Internet Camera
TV-IP672WI	Megapixel Wireless N Day / Night PTZ Internet Camera
TV-IP672PI	Megapixel PoE Day / Night PTZ Internet Camera

CONTACT INFORMATION

TRENDnet

20675 Manhattan Place,Torrance, CA 90501 USA
Tel: 1-310-961-5500
Fax: 1-310-961-5511
Web: www.trendnet.com
Email: sales@trendnet.com
1-888-326-6061

TRENDnet is a registered trademark. Other Brands and product names are trademarks of their respective holders. Information provided in this document pertain to TRENDnet products and is subject to change at any time, without notice. For the most recent product information please visit http://www.trendnet.com Copyright ©TRENDnet.All Rights Reserved.